



| TECHNICAL DATA             | PARTIAL DRAINING           |                             |       |        | CLEAN WATER(**) |        |
|----------------------------|----------------------------|-----------------------------|-------|--------|-----------------|--------|
| <b>EXTERNAL DIMENSIONS</b> |                            |                             |       |        |                 |        |
| width                      | 450 mm                     |                             |       |        |                 |        |
| depth                      | 535 mm                     |                             |       |        |                 |        |
| height                     | 715 mm                     |                             |       |        |                 |        |
| WEIGHT(basic version)      | 45.5 kg                    |                             |       |        |                 |        |
| VOLTAGE                    | 230V 50Hz                  | 230V V3 50Hz / 400V 3N 50Hz |       |        |                 |        |
| POWER REQUIRED             | 3300 W                     | 4750 W                      |       |        |                 |        |
| WATER HARDNESS             | 2-8 °F                     |                             |       |        |                 |        |
| INLET WATER PRESSURE       | 200-400 kPa                |                             |       |        |                 |        |
| <b>CROCKERY DIMENSIONS</b> |                            |                             |       |        |                 |        |
| plates diameter            | 260 mm                     |                             |       |        |                 |        |
| glasses max. height        | 260 mm                     |                             |       |        |                 |        |
| RACK DIMENSIONS            | 400X400 mm                 |                             |       |        |                 |        |
| RACK EQUIPMENT             | 2XC121 - 1X10728 - 1X15060 |                             |       |        |                 |        |
| WASHING CYCLES             | 1<90>                      | 2<120>                      | 3<60> | 4<120> | 5<150>          | 6<200> |
| <b>WATER SUPPLY 55°C</b>   |                            |                             |       |        |                 |        |
| racks/h(*) <sup>(1)</sup>  | 40                         | 30                          | 60    | 30     | 24              | 18     |
| <b>WATER SUPPLY 10°C</b>   |                            |                             |       |        |                 |        |
| racks/h(*) <sup>(1)</sup>  | 16                         | 16                          | 22    | 22     | 10              | 10     |
| WATER CONSUMPTION / CYCLE  | 2 l                        |                             | 2 l   |        | 4 l             |        |
| <b>BOILER CAPACITY</b>     | 5.2 l                      |                             |       |        |                 |        |
| BOILER HEATING ELEMENT     | 3000 W                     | 4500 W                      |       |        |                 |        |
| RINSING TEMPERATURE (SET)  | 85°C                       |                             | 70°C  |        | 85°C            |        |
| TANK CAPACITY              | 7 l                        |                             |       |        | 4 l             |        |
| TANK HEATING ELEMENT       | 1100W                      |                             |       |        |                 |        |
| TANK TEMPERATURE (SET)     | 60°C                       |                             |       |        |                 |        |
| washing/rinsing PUMPS      | 250/250 W                  |                             |       |        |                 |        |
| DRAIN PUMP                 | 25 W h max draining 0.5 m  |                             |       |        |                 |        |
| NOISE                      | 59,9±0.7 dB(A)             |                             |       |        |                 |        |

(\*) STANDARD TERMOSTOP (\*\*)TOTAL DRAINING EVERY CYCLE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.